

Model	HM-300	HM-350	HM-400
<b>Input Data (DC)</b>			
Commonly used module power (W)	240~380	280~440	320~500
Module compatibility	60-cell or 72-cell PV modules	60-cell or 72-cell PV modules	60-cell or 72-cell PV modules
Peak power MPPT voltage range (V)	29~48	33~48	34~48
Start-up voltage (V)	22	22	22
Operating voltage range (V)	16~60	16~60	16~60
Maximum input voltage	60	60	60
Maximum input current	11.5	11.5	12.5
<b>Output Data (AC)</b>			
Rated output power (VA)	300	350	400
Rated output current (A)	1.36/1.30/1.25	1.59/1.52/1.46	1.82/1.74/1.67
Nominal output voltage (V)	220/230/240	220/230/240	220/230/240
Nominal output voltage range (V)	180-275	180-275	180-275
Nominal frequency/range (V)	50/45-55 or 60/55-65	50/45-55 or 60/55-65	50/45-55 or 60/55-65
Power factor (adjustable)	>0.99 default 0.8 leading...0.8 lagging	>0.99 default 0.8 leading...0.8 lagging	>0.99 default 0.8 leading...0.8 lagging
Total harmonic distortion	<3%	<3%	<3%
Maximum units per branch	16/16/16	14/14/14	12/12/12
<b>Efficiency</b>			
CEC peak efficiency	96.70%	96.70%	96.70%
CEC weighted efficiency	96.50%	96.50%	96.50%
Nominal MPPT efficiency	99.80%	99.80%	99.80%
Nighttime power consumption (mW)	<50	<50	<50
<b>Mechanical Data</b>			
Ambient temperature range (°C)	-40~+65		
Dimensions (WxHxD mm)	182 x 164 x 29.5		
Weight (kG)	1.98		
Enclosure rating	Outdoor-NEMA (IP67)		
Cooling	Natural convention - No fans		
<b>Features</b>			
Communication	2.4GHz Proprietary RF (Nordic)		
Monitoring	Hoymiles Monitoring System		
Compliance	VDE-R-N 4105: 2018, EN 50549-1: 2019, VFR 2019, IEC/EN 62109-1/-2, IEC/EN 61000-6-1/-2/-3/-4, IEC/EN 61000-3-2/-3		